

**"U.S. PUBLIC LAND SURVEY MONUMENT RECORD"
OZAUKEE COUNTY, WISCONSIN**

TYPE OF MONUMENT: 3/4" X 21' ALUMINUM ROD

STATE PLANE COORDINATES: N: 512680.62

E: 2528856.98

ELEVATION: 868.49 M.S.L. DATUM: 1929

THETA ANGLE: _____

FIELD BOOK: 3 PAGE: 32

FIELDWORK BY: 1996 - Tom Genske and Kapur and Associates

RECORD DRAWN BY: MARK BANTON

CONTROL ACCURACY:


HORIZONTAL: 3RD ORDER, CLASS 1 VERTICAL: 3RD ORDER

CORNER INDEX No. 546

SECTION 29

TOWNSHIP 11

RANGE 21



LOCATION

SEAL:

BASIS OF MONUMENT LOCATION

1996 - Tom Genske, Ozaukee County Surveyor, Set 3/4" x 21' aluminum rod on a straight line intersection

1998 - Kapur and Associates established co-ordinates as part of Ozaukee County remonumentation program.



DATA SHOWN HEREON IS CERTIFIED AS CORRECT:

Mark Banton
Ozaukee County Surveyor

DATE: 19 Dec 08

TIE SKETCH

R/R SPIKE
S/W 10" TAMARACK
AT GRD

DHN/ DISC
W/S5" TAMARACK TREE
2.5' ABOVE GRD

DHN/ DISC
S/S4" CEDAR TREE
2.5' ABOVE GRD

DHN/ DISC
N/S56" TAMARACK TREE
2.5' ABOVE GRD

DHN/ DISC
W/S 3" CEDAR TREE
2.5' ABOVE GRD

- A = 18.71' @ 15°
- B = 25.82' @ 80°
- C = 13.72' @ 163°
- D = 17.36' @ 274°
- E = 7.73' @ 339°44'

MONUMENT LEGEND

- = BERNTSEN MONUMENT (SEE TYPE OF MON. ABOVE)
- = CONCRETE MONUMENT w/ BRASS CAP
- = CONCRETE MONUMENT w/ CROSS
- = 5/8" REBAR WITH ALUMINUM CAP

MAINTENANCE RECORD

DATE	BY WHOM	REMARKS
DEC 2008	M. BANTON	Redraw from tie sheet and re-number corner